

Camera Specification	Model	Picture	Networking Specifications
30M Standard HD IP IR Bullet Camera			
<ul style="list-style-type: none"> ☆.Aptina 1/3.2",2.0-Megapixels CMOS, 1600H*1200W Pixels ☆.Varifocal Lens 2.8-12mm, External Lens Adjustable ☆.Mechanical ICR Synchronous True D/N ☆.Min. illumination 0.5Lux Color; 0Lux IR On ☆.Output Video Resolution 1280*720 (16:9), 25FPS Max. ☆.48pcs 5mm IR LED, IR Illumination:30m ☆.Output Interface RJ45, BNC ☆.Powersupply DC12V, Support P.o.E(Optional) ☆.Operation Temperature -10℃~+55℃ ☆.Dimension(L*W*H) 259.92mm*88.2mm*123mm ☆.Waterproof Metal Housing IP66 	<p><u>CM-CN316P-1P</u></p> <p>NEW!!!</p>		<ul style="list-style-type: none"> ☆.Video Compression H.264 High Profile, MJPEG. ☆.Support Dual Stream: Primary Stream 1280*720P, Secondary Stream 320*240(CIF). ☆.Standard Onvif 1.1, Support Milestone & Nuoo System. ☆.Support Mobile Viewer: iPhone, Android. ☆.Built With Web Server, Support IE, Firefox Web Browser. ☆.Support Motion Detection, 2-way audio(Optional), Privacy Mask, Alarm Event, DDNS, RTSP, SMTP Server. ☆.Free User Friendly Client Software (for PC). ☆.Extended RS485 Port(Optional)
<ul style="list-style-type: none"> ☆.Aptina 1/3.2",2.0-Megapixels CMOS, 1600H*1200W Pixels ☆.Megapixel Fixed Lens 4mm/6mm/8mm/12mm ☆.Mechanical ICR Synchronous True D/N ☆.Min. illumination 0.5Lux Color; 0Lux IR On ☆.Output Video Resolution 1280*720 (16:9), 25FPS Max. ☆.72pcs 5mm IR LED IR Illumination:30m ☆.Output Interface RJ45, BNC ☆.Powersupply DC12V, Support P.o.E(Optional) ☆.Operation Temperature -10℃~+55℃ ☆.Dimension(L*W*H) 255mm*101mm*190mm ☆.Waterproof Metal Housing IP66 	<p><u>CM-CN318G-1P</u></p> <p>NEW!!!</p>		<ul style="list-style-type: none"> ☆.Video Compression H.264 High Profile, MJPEG. ☆.Support Dual Stream: Primary Stream 1280*720P, Secondary Stream 320*240(CIF). ☆.Standard Onvif 1.1, Support Milestone & Nuoo System. ☆.Support Mobile Viewer: iPhone, Android. ☆.Built With Web Server, Support IE, Firefox. ☆.Support Motion Detection, 2-way audio(Optional), Privacy Mask, Alarm Event, DDNS, RTSP, SMTP Server. ☆.Free User Friendly Client Software (for PC). ☆.Extended RS485 Port(Optional)
50M Standard HD IP IR Bullet Camera			
<ul style="list-style-type: none"> ☆.Aptina 1/3.2",2.0-Megapixels CMOS, 1600H*1200W Pixels ☆.Megapixel Fixed Lens 4mm/6mm/8mm/12mm/16mm ☆.Mechanical ICR Synchronous True D/N ☆.Min. illumination 0.5Lux Color; 0Lux IR On ☆.Output Video Resolution 1280*720 (16:9), 25FPS Max. ☆.2pcs Array IR LED, IR Illumination 50m ☆.Output Interface RJ45, BNC ☆.Powersupply DC12V, Support P.o.E(Optional) ☆.Operation Temperature -10℃~+55℃ ☆.Dimension(L*W*H) 150mm*140mm*94.5mm ☆.Waterproof Metal Housing IP66 	<p><u>CM-CN317GZR-1P</u></p> <p>NEW!!!</p>		<ul style="list-style-type: none"> ☆.Video Compression H.264 High Profile, MJPEG. ☆.Support Dual Stream: Primary Stream 1280*720P, Secondary Stream 320*240(CIF). ☆.Standard Onvif 1.1, Support Milestone & Nuoo System. ☆.Support Mobile Viewer: iPhone, Android. ☆.Built With Web Server, Support IE, Firefox Web Browser. ☆.Support Motion Detection, 2-way audio(Optional), Privacy Mask, Alarm Event, DDNS, RTSP, SMTP Server. ☆.Free User Friendly Client Software (for PC). ☆.Extended RS485 Port(Optional)
<ul style="list-style-type: none"> ☆.Aptina 1/3.2",2.0-Megapixels CMOS, 1600H*1200W Pixels ☆.Megapixel Fixed Lens 4mm/6mm/8mm/12mm/16mm ☆.Mechanical ICR Synchronous True D/N ☆.Min. illumination 0.5Lux Color; 0Lux IR On ☆.Output Video Resolution 1280*720 (16:9), 25FPS Max. ☆.40pcs 8mm IR LED, IR Illumination 50m ☆.Output Interface RJ45, BNC ☆.Powersupply DC12V, Support P.o.E(Optional) ☆.Operation Temperature -10℃~+55℃ ☆.Dimension(L*W*H) 150mm*140mm*94.5mm ☆.Waterproof Metal Housing IP66 	<p><u>CM-CN317G-1P</u></p>		<ul style="list-style-type: none"> ☆.Video Compression H.264 High Profile, MJPEG. ☆.Support Dual Stream: Primary Stream 1280*720P, Secondary Stream 320*240(CIF). ☆.Standard Onvif 1.1, Support Milestone & Nuoo System. ☆.Support Mobile Viewer: iPhone, Android. ☆.Built With Web Server, Support IE, Firefox Web Browser. ☆.Support Motion Detection, 2-way audio(Optional), Privacy Mask, Alarm Event, DDNS, RTSP, SMTP Server. ☆.Free User Friendly Client Software (for PC). ☆.Extended RS485 Port(Optional)
<ul style="list-style-type: none"> ☆.Aptina 1/3.2",2.0-Megapixels CMOS, 1600H*1200W Pixels ☆.Megapixel Fixed Lens 4mm/6mm/8mm/12mm/16mm ☆.Mechanical ICR Synchronous True D/N ☆.Min. illumination 0.5Lux Color; 0Lux IR On ☆.Output Video Resolution 1280*720 (16:9), 25FPS Max. ☆.35pcs 8mm IR LED, IR Illumination 50m ☆.Output Interface RJ45, BNC ☆.Powersupply DC12V, Support P.o.E(Optional) ☆.Operation Temperature -10℃~+55℃ ☆.Dimension(L*W*H) 115.5mm*99mm*81.6mm ☆.Waterproof Metal Housing IP66 	<p><u>CM-CN318K-1P</u></p> <p>NEW!!!</p>		<ul style="list-style-type: none"> ☆.Video Compression H.264 High Profile, MJPEG. ☆.Support Dual Stream: Primary Stream 1280*720P, Secondary Stream 320*240(CIF). ☆.Standard Onvif 1.1, Support Milestone & Nuoo System. ☆.Support Mobile Viewer: iPhone, Android. ☆.Built With Web Server, Support IE, Firefox Web Browser. ☆.Support Motion Detection, 2-way audio(Optional), Privacy Mask, Alarm Event, DDNS, RTSP, SMTP Server. ☆.Free User Friendly Client Software (for PC). ☆.Extended RS485 Port(Optional)
<ul style="list-style-type: none"> ☆.Aptina 1/3.2",2.0-Megapixels CMOS, 1600H*1200W Pixels ☆.Megapixel Fixed Lens 4mm/6mm/8mm/12mm/16mm ☆.Mechanical ICR Synchronous True D/N ☆.Min. illumination 0.5Lux Color; 0Lux IR On ☆.Output Video Resolution 1280*720 (16:9), 25FPS Max. ☆.35pcs 8mm IR LED, IR Illumination 50m ☆.Output Interface RJ45, BNC ☆.Powersupply DC12V, Support P.o.E(Optional) ☆.Operation Temperature -10℃~+55℃ ☆.Dimension(L*W*H) 173.5mm*101mm*92mm ☆.Waterproof Metal Housing IP66 	<p><u>CM-CN316B-1P</u></p>		<ul style="list-style-type: none"> ☆.Video Compression H.264 High Profile, MJPEG. ☆.Support Dual Stream: Primary Stream 1280*720P, Secondary Stream 320*240(CIF). ☆.Standard Onvif 1.1, Support Milestone & Nuoo System. ☆.Support Mobile Viewer: iPhone, Android. ☆.Built With Web Server, Support IE, Firefox Web Browser. ☆.Support Motion Detection, 2-way audio(Optional), Privacy Mask, Alarm Event, DDNS, RTSP, SMTP Server. ☆.Free User Friendly Client Software (for PC). ☆.Extended RS485 Port(Optional)
<ul style="list-style-type: none"> ☆.Aptina 1/3.2",2.0-Megapixels CMOS, 1600H*1200W Pixels ☆.Megapixel Fixed Lens 4mm/6mm/8mm/12mm/16mm ☆.Mechanical ICR Synchronous True D/N ☆.Min. illumination 0.5Lux Color; 0Lux IR On ☆.Output Video Resolution 1280*720 (16:9), 25FPS Max. ☆.2pcs Array IR LED, IR Illumination 50m ☆.Output Interface RJ45, BNC ☆.Powersupply DC12V, Support P.o.E(Optional) ☆.Operation Temperature -10℃~+55℃ ☆.Dimension(L*W*H) 210mm*130mm*99mm (without bracket) 	<p><u>CM-CN317BZR-1P</u></p> <p>NEW!!!</p>		<ul style="list-style-type: none"> ☆.Video Compression H.264 High Profile, MJPEG. ☆.Support Dual Stream: Primary Stream 1280*720P, Secondary Stream 320*240(CIF). ☆.Standard Onvif 1.1, Support Milestone & Nuoo System. ☆.Support Mobile Viewer: iPhone, Android. ☆.Built With Web Server, Support IE, Firefox Web Browser. ☆.Support Motion Detection, 2-way audio(Optional), Privacy Mask, Alarm Event, DDNS, RTSP, SMTP Server. ☆.Free User Friendly Client Software (for PC). ☆.Extended RS485 Port(Optional)

<ul style="list-style-type: none"> ☆.Aptina 1/3.2",2.0-Megapixels CMOS, 1600H*1200W Pixels ☆.Megapixel Fixed Lens 4mm\6mm\8mm\12mm\16mm ☆.Mechanical ICR Synchronous True D/N ☆.Min. illumination 0.5Lux Color; 0Lux IR On ☆.Output Video Resolution 1280*720 (16:9), 25FPS Max. ☆.2pcs Array IR LED, IR Illumination 50m ☆.Output Interface RJ45, BNC ☆.Powersupply DC12V, Support P.o.E(Optional) ☆.Operation Temperature -10℃~+55℃ ☆.Dimension(L*W*H) 196mm*110mm*112mm ☆.Waterproof Metal Housing IP66 	<p style="text-align: center;"><u>CM-CN316MZR-1P</u></p> <p style="text-align: center;">NEW!!!</p>		<ul style="list-style-type: none"> ☆.Video Compression H.264 High Profile, MJPEG. ☆.Support Dual Stream: Primary Stream 1280*720P, Secondary Stream 320*240(CIF). ☆.Standard Onvif 1.1, Support Milestone & Nuoo System. ☆.Support Mobile Viewer: iPhone, Andriod. ☆.Built With Web Server, Support IE, Firefox Web Browser. ☆.Support Motion Detection, 2-way audio(Optional), Privacy Mask, Alarm Event, DDNS, RTSP, SMTP Server. ☆.Free User Friendly Client Software (for PC). ☆.Extended RS485 Port(Optional)
80M Standard HD IP IR Bullet Camera			
<ul style="list-style-type: none"> ☆.Aptina 1/3.2",2.0-Megapixels CMOS, 1600H*1200W Pixels ☆.Megapixel Fixed Lens 4mm\6mm\8mm\12mm\16mm ☆.Mechanical ICR Synchronous True D/N ☆.Min. illumination 0.5Lux Color; 0Lux IR On ☆.Output Video Resolution 1280*720 (16:9), 25FPS Max. ☆.4pcs Array IR LED, IR Illumination 80m ☆.Output Interface RJ45, BNC ☆.Powersupply DC12V, Support P.o.E(Optional) ☆.Operation Temperature -10℃~+55℃ ☆.Dimension(L*W*H) 284mm*152mm*232mm ☆.Waterproof Metal Housing IP66 	<p style="text-align: center;"><u>CM-CN318FZR-1P</u></p> <p style="text-align: center;">NEW!!!</p>		<ul style="list-style-type: none"> ☆.Video Compression H.264 High Profile, MJPEG. ☆.Support Dual Stream: Primary Stream 1280*720P, Secondary Stream 320*240(CIF). ☆.Standard Onvif 1.1, Support Milestone & Nuoo System. ☆.Support Mobile Viewer: iPhone, Andriod. ☆.Built With Web Server, Support IE, Firefox Web Browser. ☆.Support Motion Detection, 2-way audio(Optional), Privacy Mask, Alarm Event, DDNS, RTSP, SMTP Server. ☆.Free User Friendly Client Software (for PC). ☆.Extended RS485 Port(Optional)
30M Standard HD IP IR Dome Camera			
<ul style="list-style-type: none"> ☆.Aptina 1/3.2",2.0-Megapixels CMOS, 1600H*1200W Pixels ☆.Megapixel Varifocal/Fixed Lens 2.8-12mm\4mm\6mm\8mm ☆.Mechanical ICR Synchronous True D/N ☆.Min. illumination 0.5Lux Color; 0Lux IR On ☆.Output Video Resolution 1280*720 (16:9), 25FPS Max. ☆.30pcs 5mm IR LED, IR Illumination 30m ☆.Output Interface RJ45, BNC ☆.Powersupply DC12V, Support P.o.E(Optional) ☆.Operation Temperature -10℃~+55℃ ☆.Dimension(L*W*H) 137.4mm*103.6mm (without bracket) ☆.Vandalproof Metal Housing IP65 	<p style="text-align: center;"><u>CM-CN619QIR-1P</u></p> <p style="text-align: center;">NEW!!!</p>		<ul style="list-style-type: none"> ☆.Video Compression H.264 High Profile, MJPEG. ☆.Support Dual Stream: Primary Stream 1280*720P, Secondary Stream 320*240(CIF). ☆.Standard Onvif 1.1, Support Milestone & Nuoo System. ☆.Support Mobile Viewer: iPhone, Andriod. ☆.Built With Web Server, Support IE, Firefox Web Browser. ☆.Support Motion Detection, 2-way audio(Optional), Privacy Mask, Alarm Event, DDNS, RTSP, SMTP Server. ☆.Free User Friendly Client Software (for PC). ☆.Extended RS485 Port(Optional)
<ul style="list-style-type: none"> ☆.Aptina 1/3.2",2.0-Megapixels CMOS, 1600H*1200W Pixels ☆.Megapixel Varifocal Lens 4-9mm, External Lens Adjustable ☆.Mechanical ICR Synchronous True D/N ☆.Min. illumination 0.5Lux Color; 0Lux IR On ☆.Output Video Resolution 1280*720 (16:9), 25FPS Max. ☆.36pcs 5mm IR LED, IR Illumination 30m ☆.Output Interface RJ45, BNC ☆.Powersupply DC12V, Support P.o.E(Optional) ☆.Operation Temperature -10℃~+55℃ ☆.Dimension(L*W*H) 119mm*100mm 	<p style="text-align: center;"><u>CM-CN61B-1P</u></p> <p style="text-align: center;">NEW!!!</p>		<ul style="list-style-type: none"> ☆.Support Dual Stream: Primary Stream 1280*720P, Secondary Stream 320*240(CIF). ☆.Standard Onvif 1.1, Support Milestone & Nuoo System. ☆.Support Mobile Viewer: iPhone, Andriod. ☆.Built With Web Server, Support IE, Firefox Web Browser. ☆.Support Motion Detection, 2-way audio(Optional), Privacy Mask, Alarm Event, DDNS, RTSP, SMTP Server. ☆.Free User Friendly Client Software (for PC). ☆.Extended RS485 Port(Optional)
<ul style="list-style-type: none"> ☆.Aptina 1/3.2",2.0-Megapixels CMOS, 1600H*1200W Pixels ☆.Megapixel Fixed Lens 4mm\6mm\8mm ☆.Mechanical ICR Synchronous True D/N ☆.Min. illumination 0.5Lux Color; 0Lux IR On ☆.Output Video Resolution 1280*720 (16:9), 25FPS Max. ☆.42pcs 5mm IR LED, IR Illumination 30m ☆.Output Interface RJ45, BNC ☆.Powersupply DC12V, Support P.o.E(Optional) ☆.Operation Temperature -10℃~+55℃ ☆.Dimension(L*W*H) 139.5mm*109.3mm ☆.Vandalproof Metal Housing IP66 	<p style="text-align: center;"><u>CM-CN61S-1P</u></p> <p style="text-align: center;">NEW!!!</p>		<ul style="list-style-type: none"> ☆.Video Compression H.264 High Profile, MJPEG. ☆.Support Dual Stream: Primary Stream 1280*720P, Secondary Stream 320*240(CIF). ☆.Standard Onvif 1.1, Support Milestone & Nuoo System. ☆.Support Mobile Viewer: iPhone, Andriod. ☆.Built With Web Server, Support IE, Firefox Web Browser. ☆.Support Motion Detection, 2-way audio(Optional), Privacy Mask, Alarm Event, DDNS, RTSP, SMTP Server. ☆.Free User Friendly Client Software (for PC). ☆.Extended RS485 Port(Optional)